## NSN 5930-01-337-4724

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-337-4724

| Body Style:  |  |  |
|--|--|--|
| Printed circuit  |  |  |
| Hazardous Locations/environmental Protection:                      |  |  |
| Dustproof  |  |  |
| Overall Length:  |  |  |
| 0.320 inches   |  |  |
| Overall Height:  |  |  |
| 1.012 inches   |  |  |
| Overall Width:   |  |  |
| 0.330 inches   |  |  |
| Body Length:   |  |  |
| 0.320 inches   |  |  |
| Body Width:  |  |  |
| 0.200 inches   |  |  |
| Body Height:   |  |  |
| 0.560 inches   |  |  |
| Case Material:   |  |  |
| Plastic  |  |  |
| Actuator Style:  |  |  |
| Round  |  |  |
| Actuator Diameter:   |  |  |
| 0.100 inches   |  |  |
| Actuator Height:   |  |  |
| 0.410 inches   |  |  |
| Actuator Position-action Relationship:                             |  |  |
| Up position maintained and down position maintained                |  |  |
| Maximum Voltage Rating In Volts:                                   |  |  |
| 20.0 ac and 20.0 dc  |  |  |
| Inclosure Type:  |  |  |
| Fully enclosed   |  |  |
| Mounting Method:   |  |  |
| Printed circuit  |  |  |
| Nonpile-up Contact Arrangement:                                    |  |  |
| 1 pole, double throw, both positions maintained single switch unit |  |  |
| Contact Load Current Rating At Maximum Rated Voltage:              |  |  |
| 20.0 milliamperes resistive ac and 20.0 milliamperes resistive dc  |  |  |
| Special Features:  |  |  |
| Unthreaded bushing   |  |  |
| Precious Material And Location:                                    |  |  |
| Contact and terminal surfaces gold                                 |  |  |
| Terminal Type And Quantity:  |  |  |

3 printed circuit

## **NSN 5930-01-337-4724** Toggle Switch - Page 2 of 2



|  | Life: |
|--|-------|
|  |       |
|  |       |

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0