

View Online at <https://aerobasegroup.com/nsn/5930-01-337-4975>

Thread Class:

2a single mounting facility

Thread Length:

0.315 inches single mounting facility

Overall Length:

3.205 inches

First Flat Length:

1.500 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.500 inches single actuator

Overall Diameter:

1.031 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

12 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest ac voltage rating at sea level110.0 lowest ac voltage rating at sea level250.0 highest dc voltage rating at sea level110.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

150.0 milliamperes resistive load highest ac voltage rating at sea level350.0 milliamperes resistive load lowest ac voltage rating at sea level150.0 milliamperes resistive load highest dc voltage rating at sea level350.0 milliamperes resistive load lowest dc voltage rating at sea level

Precious Material And Location:

Contacts, terminal and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Snap or line

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0