

View Online at <https://aerobasegroup.com/nsn/5930-01-337-6110>

Thread Class:

2a single mounting facility

Thread Length:

0.235 inches single mounting facility and 0.265 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

Overall Length:

Between 0.860 inches and 0.940 inches

First Flat Length:

0.275 inches single actuator

Flat Height:

0.079 inches single actuator and 0.109 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.295 inches single actuator and 0.325 inches single actuator

Overall Diameter:

Between 0.315 inches and 0.325 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock flatted bushing at 9: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+3.000/+6.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0