

View Online at <https://aerobasegroup.com/nsn/5930-01-338-0136>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Fungus resistant and humidity resistant and shock resistant and vibration resistant and watertight

**Overall Length:**

1.696 inches

**Body Diameter:**

0.437 inches

**Bushing Length:**

Between 0.245 inches and 0.255 inches

**Body Length:**

Between 0.755 inches and 0.785 inches

**Overall Diameter:**

0.460 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.375 inches

**Actuator Height:**

0.454 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**End Application:**

5895-01-177-0791 receiver-transm

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing w/panel seal

**Features Provided:**

Full display lens

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

250.0 milliamperes resistive dc and 250.0 milliamperes resistive ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0