

View Online at <https://aerobasegroup.com/nsn/5930-01-338-3197>

**Hazardous Locations/environmental Protection:**

Shock proof and watertight

**Overall Length:**

3.840 inches

**Overall Height:**

6.250 inches

**Overall Width:**

3.750 inches

**Unthreaded Mounting Hole Diameter:**

0.280 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.500 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Flange single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and metallic inclosure

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level115.0 lowest ac voltage rating at sea level355.0 highest dc voltage rating at sea level115.0 lowest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes inductive load highest ac voltage rating at sea level6.0 amperes inductive load lowest ac voltage rating at sea level500.0 milliamperes inductive load highest dc voltage rating at sea level2.0 amperes inductive load lowest dc voltage rating at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0