NSN 5930-01-338-3558

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-338-3558

Inside Diameter: 0.250 inches single connection **Hazardous Locations/environmental Protection:** Corrosion resistant **Overall Length: 3.688** inches **Overall Height:** 4.062 inches **Overall Width: 3.438** inches **Body Length: 3.688** inches **Body Height:** 3.000 inches **Pressure Switch Type:** Gage **Mounting Method:** Inlet connection **Features Provided:** Electrical access port **Contact Action Stimulus:** Increase **Thread Size:** 0.250 inches single pressure connection **Nonpile-up Contact Arrangement:** 2 pole, single throw, normally open, double make, momentary action **Terminal Type:** Screw **Contact Load Current Rating:** 2.0 amperes resistive load first voltage3.0 amperes resistive load second voltage2.0 amperes resistive load third voltage2.0 amperes resistive load fourth voltage **Contact Adjustability:** Actuation point adjustable, preset **Contact Adjustment Range:** +40.00/+250.00 actuation point pounds per square inch **Contact Adjustment Type:**

External actuation point screw

Contact Stimulus Rating:

120.00 actuation point pounds per square inch and 150.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage230.0 ac at sea level second voltage115.0 dc at sea level third voltage230.0 dc at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

NSN 5930-01-338-3558

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Rectangular
Thread Series Designator:
Nptf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A048b0