

View Online at <https://aerobasegroup.com/nsn/5930-01-338-5399>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.400 inches

Overall Height:

2.732 inches

Overall Width:

1.000 inches

Bushing Length:

Between 0.439 inches and 0.501 inches

Body Length:

1.400 inches

Body Width:

1.000 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.410 inches and 0.430 inches

Actuator Height:

Between 0.969 inches and 1.031 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked in

Maximum Voltage Rating In Volts:

28.0 dc and 110.0 ac

Mounting Surface To Terminal End Distance:

1.200 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 2.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0