

View Online at <https://aerobasegroup.com/nsn/5930-01-338-5400>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Humidity resistant and shock resistant

Overall Length:

0.572 inches

Overall Height:

2.202 inches

Overall Width:

0.364 inches

Bushing Length:

0.469 inches

Body Length:

0.572 inches

Body Width:

0.364 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

Between 0.936 inches and 1.030 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

50.0 dc and 115.0 ac

Mounting Surface To Terminal End Distance:

Between 0.725 inches and 0.775 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Printed circuit and threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0