

View Online at <https://aerobasegroup.com/nsn/5930-01-338-5401>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Humidity resistant and shock resistant

**Overall Length:**

0.572 inches

**Overall Height:**

2.202 inches

**Overall Width:**

0.364 inches

**Bushing Length:**

0.469 inches

**Body Length:**

0.572 inches

**Body Width:**

0.364 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

Between 0.936 inches and 1.030 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position locked out and center position no locking action

**Maximum Voltage Rating In Volts:**

50.0 dc and 115.0 ac

**Mounting Surface To Terminal End Distance:**

Between 0.725 inches and 0.775 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Printed circuit and threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A053a0