

View Online at <https://aerobasegroup.com/nsn/5930-01-338-5494>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

2.505 inches

Body Diameter:

Between 0.970 inches and 1.030 inches

Bushing Length:

Between 0.970 inches and 1.030 inches

Overall Diameter:

Between 0.970 inches and 1.030 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

Between 0.315 inches and 0.435 inches

Actuator Free Position Height:

Between 1.345 inches and 1.405 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0