

View Online at <https://aerobasegroup.com/nsn/5930-01-338-6434>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.770 inches

Overall Height:

2.166 inches

Overall Width:

1.156 inches

Unthreaded Mounting Hole Diameter:

0.100 inches 1st mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.600 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches 1st mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

5895-01-317-6232 demodulator

Mounting Method:

Bracket 1st mounting facility and unthreaded hole 1st mounting facilityprinted circuit 2nd mounting facility

Actuator Type:

Lever all actuators

Contact Voltage Rating In Volts:

28.0 ac at sea level28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

Contact Arrangement Truth Table:

Bcd, separate common to not-true bits, 2 pole - 10 positions each section

Color:

Black each bodyblack each indicator backgroundwhite each indicator marking

Precious Material And Location:

Printed circuit board circuit surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0