## NSN 5930-01-338-6437



Toggle Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-338-6437 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 0.500 inches **Overall Height:** 1.495 inches **Overall Width:** 0.270 inches **Bushing Length:** 0.350 inches **Body Length:** 0.500 inches **Body Width:** 0.270 inches **Body Height:** 0.350 inches **Case Material:** Plastic **Actuator Style:** Round **Actuator Diameter:** 0.130 inches **Actuator Height:** 0.640 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained **Maximum Voltage Rating In Volts:** 28.0 dc and 250.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 40 **Thread Size:** 

0.250 inches

## **Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

## NSN 5930-01-338-6437

Toggle Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage	Contact	Load	Current	Rating A	At Maximum	Rated	Voltage
--	---------	------	---------	----------	------------	-------	---------

2.000 amperes resistive dc and 2.000 amperes resistive ac

**Precious Material And Location:** 

Contact and terminal surfaces silver

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0