

View Online at <https://aerobasegroup.com/nsn/5930-01-338-6440>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Driptight and shock resistant and vibration resistant

**Overall Length:**

1.680 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Case Material:**

Metal

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.130 inches and 0.230 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Amber single actuator

**Actuator Inscription:**

A fault b fault single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Mounting Surface To Terminal End Distance:**

1.500 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Horizontal split lens

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0