

View Online at <https://aerobasegroup.com/nsn/5930-01-339-2126>

Thread Class:

2a

Body Style:

Bushing mounted

Body Diameter:

0.625 inches

Bushing Length:

Between 0.595 inches and 0.655 inches

Body Length:

1.500 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.245 inches and 0.255 inches

Actuator Height:

0.250 inches

Actuator Free Position Height:

Between 0.845 inches and 0.905 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing w/panel seal

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Specification Data:

99167-5905513 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0