

View Online at <https://aerobasegroup.com/nsn/5930-01-339-2126>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Body Diameter:**

0.625 inches

**Bushing Length:**

Between 0.595 inches and 0.655 inches

**Body Length:**

1.500 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.245 inches and 0.255 inches

**Actuator Height:**

0.250 inches

**Actuator Free Position Height:**

Between 0.845 inches and 0.905 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing w/panel seal

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

144.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 wire lead

**Specification Data:**

99167-5905513 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0