

View Online at <https://aerobasegroup.com/nsn/5930-01-339-2127>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.623 inches and 0.627 inches

Body Length:

1.670 inches

Body Width:

0.630 inches

Body Height:

0.970 inches

Unthreaded Mounting Hole Diameter:

Between 0.1259 inches and 0.1307 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.125 inches

Actuator Length:

0.880 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.150 inches

Actuator Roller Diameter:

0.190 inches

Actuator Roller Width:

0.190 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

26.0 ounces

Actuator Movement:

0.080 pretravel inches and 0.030 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0