## NSN 5930-01-339-2127

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-339-2127

Body Style:				
Hole mounted				
Center To Center Distance Between Mounting Facilities Parallel To Length:				
Between 0.623 inches and 0.627 inches				
Body Length:				
1.670 inches				
Body Width:				
0.630 inches				
Body Height:				
0.970 inches				
Unthreaded Mounting Hole Diameter:				
Between 0.1259 inches and 0.1307 inches				
Center To Center Distance Between Mounting Facilities Parallel To Height:				
0.125 inches				
Actuator Length:				
0.880 inches				
Actuator Style:				
Roller arm				
Actuator Free Position Height:				
1.150 inches				
Actuator Roller Diameter:				
0.190 inches				
Actuator Roller Width:				
0.190 inches				
Maximum Voltage Rating In Volts:				
250.0 ac				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Unthreaded hole				
Nonpile-up Contact Arrangement:				
1 pole, single throw, normally open, momentary action single switch unit				
Switch Release Force:				
4.0 ounces				
Switch Actuating Force:				
26.0 ounces				
Actuator Movement:				
0.080 pretravel inches and 0.030 overtravel inches and 0.016 differential inches				
Contact Load Current Rating At Maximum Rated Voltage:				
10 000 amperes resistive ac				

Contacts silver

**Precious Material And Location:** 

## NSN 5930-01-339-2127

Sensitive Switch - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0