

View Online at <https://aerobasegroup.com/nsn/5930-01-339-2439>

Thread Class:

2a 2nd mounting facility

Thread Length:

0.260 inches 2nd mounting facility

Overall Length:

1.470 inches

Shaft Diameter:

0.130 inches single actuator

Shaft Length:

0.750 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 6: 00 o'clock flatted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Printed circuit 1st mounting facility threaded bushing 2nd mounting facility

Thready Qty Per Inch (tpi):

40 2nd mounting facility

Thread Size:

0.250 inches 2nd mounting facility

Contact Voltage Rating In Volts:

20.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

20.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Snap or line

Thread Series Designator:

Uns 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0