NSN 5930-01-339-5080

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-339-5080

View Online at https://aerobasegroup.com/nsn/5930-01-339-5080
Thread Class:
2a single threaded bushing
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.633 inches
Body Diameter:
0.170 inches
Body Length:
2.520 inches
Tempurature Sensing Element Type:
Internal sensor
Width Across Flats:
0.890 inches
Mounting Method:
Immersion well and threaded bushing
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
2.0 amperes resistive load first voltage and 1.0 amperes inductive load first voltage and 0.5 amperes lamp load first voltage2.0 amperes
resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
400.00 actuation point degrees fahrenheit and 390.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
115.0 ac at sea level first voltage28.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical w/flange

N/a

Shelf Life:

Thread Series Designator: Unf single threaded bushing

NSN 5930-01-339-5080

Thermostatic Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A048b0