# NSN 5930-01-339-5080

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-339-5080

## **Thread Class:**

2a single threaded bushing

## Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

4.633 inches

## **Body Diameter:**

0.170 inches

#### **Body Length:**

2.520 inches

#### **Tempurature Sensing Element Type:**

Internal sensor

Width Across Flats:

0.890 inches

#### Mounting Method:

Immersion well and threaded bushing

#### **Features Provided:**

Hermetically sealed case

#### **Contact Action Stimulus:**

Increase

Thread Size:

0.250 inches single threaded bushing

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

#### **Terminal Type:**

Connector, receptacle

#### **Contact Load Current Rating:**

2.0 amperes resistive load first voltage and 1.0 amperes inductive load first voltage and 0.5 amperes lamp load first voltage2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage

#### Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

#### **Contact Stimulus Rating:**

400.00 actuation point degrees fahrenheit and 390.00 deactuation point degrees fahrenheit

#### **Contact Voltage Rating In Volts:**

115.0 ac at sea level first voltage28.0 dc at sea level second voltage

#### Media For Which Designed:

Gas or liquid

#### Style Designator:

Cylindrical w/flange

#### **Thread Series Designator:**

Unf single threaded bushing

## Shelf Life:

N/a

# NSN 5930-01-339-5080

Thermostatic Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

