

View Online at <https://aerobasegroup.com/nsn/5930-01-339-6652>

Thread Length:

0.362 inches single threaded bushing and 0.422 inches single threaded bushing

Overall Length:

Between 2.080 inches and 2.170 inches

Body Diameter:

0.310 inches

Body Length:

Between 1.970 inches and 2.030 inches

End Application:

An/sps-40c fc, radar set

Temperature Sensing Element Type:

Bulb

Width Across Flats:

0.500 inches

Mounting Method:

Threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.125 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

1.0 amperes resistive load first voltage and 500.0 milliamperes inductive load first voltage and 200.0 milliamperes lamp load first voltage
1.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage and 200.0 milliamperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

105.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage 28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/flange

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Specification Data:

81349-mil-s-24236/11 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0