

View Online at <https://aerobasegroup.com/nsn/5930-01-339-6657>

**Body Style:**

Hole mounted

**Overall Length:**

0.781 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Overall Height:**

0.861 inches

**Overall Width:**

0.438 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.761 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Length:**

0.125 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.100 inches

**Actuator Width:**

0.125 inches

**Actuator Free Position Height:**

Between 0.386 inches and 0.406 inches

**Maximum Voltage Rating In Volts:**

28.0 dc and 250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 8.0 ounces and 16.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.012 overtravel inches and 0.015 differential inches and 0.035 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 7.000 amperes resistive ac

**Precious Material And Location:**

Contact surfaces gold

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0