

View Online at <https://aerobasegroup.com/nsn/5930-01-339-6657>

Body Style:

Hole mounted

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

0.861 inches

Overall Width:

0.438 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.761 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Length:

0.125 inches

Actuator Style:

Rectangular

Actuator Height:

0.100 inches

Actuator Width:

0.125 inches

Actuator Free Position Height:

Between 0.386 inches and 0.406 inches

Maximum Voltage Rating In Volts:

28.0 dc and 250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 8.0 ounces and 16.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.012 overtravel inches and 0.015 differential inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 7.000 amperes resistive ac

Precious Material And Location:

Contact surfaces gold

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0