

View Online at <https://aerobasegroup.com/nsn/5930-01-340-0651>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

0.790 inches

Overall Diameter:

0.470 inches

Individual Section Quantity:

1

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Terminal single mounting facility

Contact Voltage Rating In Volts:

24.0 highest dc voltage rating at sea level12.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Pin

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

300.0 milliamperes resistive load highest dc voltage rating at sea level500.0 milliamperes resistive load lowest dc voltage rating at sea level

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Miniature, pin mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0