

View Online at <https://aerobasegroup.com/nsn/5930-01-340-1278>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

0.620 inches

Overall Height:

2.600 inches

Overall Width:

0.520 inches

Bushing Length:

0.470 inches

Body Length:

0.562 inches

Body Width:

0.520 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.205 inches and 0.215 inches

Actuator Height:

1.140 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Mounting Surface To Terminal End Distance:

0.990 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

8.000 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes resistive dc and 5.000 amperes motor dc and 8.000 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac and 5.000 amperes motor ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0