

View Online at <https://aerobasegroup.com/nsn/5930-01-340-1278>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

0.620 inches

**Overall Height:**

2.600 inches

**Overall Width:**

0.520 inches

**Bushing Length:**

0.470 inches

**Body Length:**

0.562 inches

**Body Width:**

0.520 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.205 inches and 0.215 inches

**Actuator Height:**

1.140 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Mounting Surface To Terminal End Distance:**

0.990 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

8.000 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes resistive dc and 5.000 amperes motor dc and 8.000 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac and 5.000 amperes motor ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

9 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0