

View Online at <https://aerobasegroup.com/nsn/5930-01-340-2157>

**Body Style:**

Panel mount

**Body Length:**

1.200 inches

**Body Width:**

1.200 inches

**Body Height:**

3.150 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Support equipment, mx peacekeeper missile

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Press fit

**Features Provided:**

Actuator seal and rfi shielding and horizontal split lens

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac and 2.500 amperes inductive ac and 5.000 amperes resistive dc and 2.500 amperes inductive dc

**Precious Material And Location:**

Terminal surfaces gold

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

17 pin

**Specification Data:**

81349-mil-s-22885/80 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0