

View Online at <https://aerobasegroup.com/nsn/5930-01-340-5772>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture resistant and shock resistant and vibration resistant

Overall Length:

13.0 millimeters

Overall Height:

32.3 millimeters

Overall Width:

13.0 millimeters

Bushing Length:

8.0 millimeters

Body Length:

13.0 millimeters

Body Width:

13.0 millimeters

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

3.0 millimeters

Actuator Height:

10.5 millimeters

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

125.0 ac

End Application:

6625-01-257-7235 adapter, test

Mounting Surface To Terminal End Distance:

13.8 millimeters

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive ac

Precious Material And Location:

Contact surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0