

View Online at <https://aerobasegroup.com/nsn/5930-01-340-7509>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant and explosion proof

Overall Length:

Between 7.760 inches and 7.820 inches

Overall Height:

1.585 inches

Overall Width:

Between 1.120 inches and 1.180 inches

Unthreaded Mounting Hole Diameter:

0.100 inches 2nd mounting facility

Individual Section Quantity:

14

Longest Horizontal Distance Between Mounting Centers:

7.605 inches 2nd mounting facility and 7.635 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

0.890 inches 2nd mounting facility and 0.910 inches 2nd mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Mounting Method:

Printed circuit 1st mounting facility unthreaded hole 2nd mounting facility and bracket 2nd mounting facility

Features Provided:

Metallic inclosure

Contact Voltage Rating In Volts:

28.0 ac at sea level 28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Terminal Type:

Printed circuit

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0