

View Online at <https://aerobasegroup.com/nsn/5930-01-340-9136>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

Between 5.130 inches and 5.230 inches

**Overall Width:**

Between 2.760 inches and 2.860 inches

**Body Height:**

Between 2.700 inches and 2.800 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.279 inches and 0.281 inches

**Capillary Tube Length:**

36.0 inches

**Bulb Length:**

Between 3.880 inches and 4.020 inches

**Bulb Diameter:**

0.815 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 2.390 inches and 2.410 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.660 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 3.270 inches and 3.290 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Operating Temperature Rating:**

195.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

2.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+90.00/+165.00 actuation point degrees fahrenheit

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0