

View Online at <https://aerobasegroup.com/nsn/5930-01-340-9141>

Body Style:

Bushing mount

Overall Length:

0.510 inches

Overall Width:

0.386 inches

Bushing Length:

Between 0.260 inches and 0.270 inches

Body Length:

0.510 inches

Body Width:

0.275 inches

Body Height:

0.375 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.105 inches

Actuator Height:

Between 0.257 inches and 0.287 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

End Application:

Combiner-demodulator md-900a/ssr-1

Inclosure Type:

Fully enclosed

Mounting Method:

Printed circuit

Nonpile-up Contact Arrangement:

1 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contact surfaces silver and contact surfaces gold

Test Data Document:

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 printed circuit

Specification Data:

81349-mil-s-83731/15 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0