NSN 5930-01-340-9143



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-340-9143 **Thread Class:** 2b **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Corrosion resistant and shock resistant and vibration resistant and watertight **Overall Length:** 2.792 inches **Overall Height:** 3.090 inches **Overall Width:** 1.100 inches **Case Material:** Metal **Actuator Style:** Round **Actuator Diameter:** 0.700 inches **Actuator Height:** 1.090 inches **Actuator Free Position Height:** 1.090 inches **Housing Height:** 2.000 inches **Housing Length:** 1.500 inches **Housing Width:** 1.100 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 1.812 inches **Maximum Voltage Rating In Volts:** 12.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:**

0.138 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-340-9143 Sensitive Switch - Page 2 of 2



Switch Release Force:
64.0 ounces
Switch Actuating Force:
192.0 ounces
Actuator Movement:
Between 0.250 pretravel inches and 0.250 overtravel inches
Contact Load Current Rating At Maximum Rated Voltage:
1.0 milliamperes resistive dc
Thread Series Designator:
Unc
Terminal Type And Quantity:
1 connector, receptacle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0