

View Online at <https://aerobasegroup.com/nsn/5930-01-340-9969>

**Overall Length:**

1.203 inches

**Overall Height:**

0.585 inches

**Body Diameter:**

0.605 inches

**Mounting Slot Width:**

0.140 inches

**Body Height:**

0.290 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Distance Between Mounting Facility Centers:**

0.937 inches

**End Application:**

Satellite communications set an/wsc- (v) 2

**Temperature Sensing Element Type:**

Disc

**Operating Temperature Rating:**

Between -85.0 degrees fahrenheit and 500.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Threaded hole

**Contact Load Current Rating:**

2.0 amperes resistive load first voltage and 1.0 amperes inductive load first voltage and 500.0 milliamperes lamp load first voltage  
5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Stimulus Rating:**

135.00 actuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 ac at sea level first voltage  
115.0 dc at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0