

View Online at <https://aerobasegroup.com/nsn/5930-01-341-0753>

**Hazardous Locations/environmental Protection:**

Shock proof and watertight

**Overall Length:**

4.450 inches

**Overall Height:**

6.300 inches

**Overall Width:**

3.700 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.700 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Flange single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob and metallic inclosure

**Contact Voltage Rating In Volts:**

480.0 highest ac voltage rating at sea level120.0 lowest ac voltage rating at sea level250.0 highest dc voltage rating at sea level28.0 lowest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Terminal Type:**

Screw

**Contact Load Current Rating:**

3.0 amperes inductive load highest ac voltage rating at sea level10.0 amperes inductive load lowest ac voltage rating at sea level2.0 amperes inductive load highest dc voltage rating at sea level10.0 amperes inductive load lowest dc voltage rating at sea level

**Style Designator:**

Rectangular panel mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0