

View Online at <https://aerobasegroup.com/nsn/5930-01-341-0753>

Hazardous Locations/environmental Protection:

Shock proof and watertight

Overall Length:

4.450 inches

Overall Height:

6.300 inches

Overall Width:

3.700 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.700 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Flange single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

480.0 highest ac voltage rating at sea level120.0 lowest ac voltage rating at sea level250.0 highest dc voltage rating at sea level28.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Terminal Type:

Screw

Contact Load Current Rating:

3.0 amperes inductive load highest ac voltage rating at sea level10.0 amperes inductive load lowest ac voltage rating at sea level2.0 amperes inductive load highest dc voltage rating at sea level10.0 amperes inductive load lowest dc voltage rating at sea level

Style Designator:

Rectangular panel mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0