

View Online at <https://aerobasegroup.com/nsn/5930-01-341-0756>

**Thread Class:**

2a 2nd mounting facility

**Thread Length:**

0.292 inches 2nd mounting facility and 0.332 inches 2nd mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

1.416 inches

**Overall Height:**

0.867 inches

**Overall Width:**

0.725 inches

**First Flat Length:**

0.355 inches single actuator and 0.395 inches single actuator

**Flat Height:**

0.084 inches single actuator and 0.104 inches single actuator

**Shaft Diameter:**

0.198 inches single actuator and 0.208 inches single actuator

**Shaft Length:**

0.687 inches single actuator

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock flatted bushing at 9: 00 o'clock

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Printed circuit 1st mounting facility threaded bushing 2nd mounting facility

**Thread Size:**

0.250 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 single section

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Detent Rotational Torque Range:**

+5.000/+20.000 inch-ounces single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level 250.0 milliamperes inductive load dc at sea level and 500.0 milliamperes resistive load dc at sea level

**Style Designator:**

Wafer, printed board, bushing mount

**Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef 2nd mounting facility

**Specification Data:**

81349-mil-s-3786/39 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0