

View Online at <https://aerobasegroup.com/nsn/5930-01-341-0756>

Thread Class:

2a 2nd mounting facility

Thread Length:

0.292 inches 2nd mounting facility and 0.332 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.416 inches

Overall Height:

0.867 inches

Overall Width:

0.725 inches

First Flat Length:

0.355 inches single actuator and 0.395 inches single actuator

Flat Height:

0.084 inches single actuator and 0.104 inches single actuator

Shaft Diameter:

0.198 inches single actuator and 0.208 inches single actuator

Shaft Length:

0.687 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock flatted bushing at 9: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

2 single section rear

Mounting Method:

Printed circuit 1st mounting facility threaded bushing 2nd mounting facility

Thread Size:

0.250 inches 2nd mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+5.000/+20.000 inch-ounces single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level 250.0 milliamperes inductive load dc at sea level and 500.0 milliamperes resistive load dc at sea level

Style Designator:

Wafer, printed board, bushing mount

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef 2nd mounting facility

Specification Data:

81349-mil-s-3786/39 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0