NSN 5930-01-341-3243

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-341-3243

| Body Style: |
|---|
| Panel mounted |
| Hazardous Locations/environmental Protection: |
| Driptight and dustproof |
| Overall Length: |
| 2.185 inches |
| Overall Height: |
| 0.960 inches |
| Overall Width: |
| 0.960 inches |
| Body Width: |
| 0.960 inches |
| Body Height: |
| 0.960 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.510 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.445 inches |
| Actuator Width: |
| 0.510 inches |
| Actuator Color: |
| Green single actuator and red single actuator |
| Illuminated Actuator Color: |
| Green single actuator and red single actuator |
| Actuator Inscription: |
| On/off single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| End Application: |
| 5895-01-240-0577 central, communi |
| Mounting Surface To Terminal End Distance: |
| 1.910 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel and terminal |
| Features Provided: |
| Horizontal split lens |

NSN 5930-01-341-3243

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

0.024 amperes resistive dc

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0