

View Online at <https://aerobasegroup.com/nsn/5930-01-341-6893>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Shock proof and watertight

Overall Length:

3.520 inches

Overall Height:

1.740 inches

Overall Width:

2.120 inches

Individual Section Quantity:

1

Knob Manufacturer Code:

27192

Knob Manufacturer Part Number:

53-1160

Longest Horizontal Distance Between Mounting Centers:

1.620 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level115.0 lowest ac voltage rating at sea level355.0 highest dc voltage rating at sea level115.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

750.0 milliamperes inductive load highest ac voltage rating at sea level3.0 amperes inductive load lowest ac voltage rating at sea level400.0 milliamperes inductive load highest dc voltage rating at sea level1.1 amperes inductive load lowest dc voltage rating at sea level

Special Features:

Legend plate reads off remote local

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0