

View Online at <https://aerobasegroup.com/nsn/5930-01-341-7358>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

1.130 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.250 inches single actuator

**Overall Diameter:**

1.000 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 1: 00 o'clock flatted bushing at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, slotted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

100.0 milliamperes resistive load ac at sea level 20.0 milliamperes inductive load dc at sea level and 200.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Contact and rotor blade surfaces silver and contact and rotor blade surfaces gold

**Precious Material:**

Silver and gold

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0