

View Online at <https://aerobasegroup.com/nsn/5930-01-341-7358>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.130 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.250 inches single actuator

Overall Diameter:

1.000 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 1: 00 o'clock flatted bushing at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

100.0 milliamperes resistive load ac at sea level 20.0 milliamperes inductive load dc at sea level and 200.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver and contact and rotor blade surfaces gold

Precious Material:

Silver and gold

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0