

View Online at <https://aerobasegroup.com/nsn/5930-01-341-7938>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

0.450 inches

Overall Height:

Between 1.247 inches and 1.287 inches

Overall Width:

0.500 inches

Bushing Length:

Between 0.342 inches and 0.362 inches

Body Length:

0.450 inches

Body Width:

0.500 inches

Body Height:

0.410 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.105 inches and 0.125 inches

Actuator Height:

Between 0.400 inches and 0.420 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contact and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0