

View Online at <https://aerobasegroup.com/nsn/5930-01-341-9022>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Dustproof and shock resistant and vibration resistant

**Overall Length:**

3.120 inches

**Overall Height:**

1.000 inches

**Overall Width:**

1.000 inches

**Body Length:**

2.850 inches

**Body Width:**

0.920 inches

**Body Height:**

0.920 inches

**Case Material:**

Metal

**Actuator Length:**

0.640 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.270 inches

**Actuator Width:**

0.640 inches

**Actuator Color:**

Black single actuator and gray single actuator

**Illuminated Actuator Color:**

Black single actuator and gray single actuator

**Actuator Inscription:**

Battle short/on single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal and horizontal split lens

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

Inscription appears red when illuminated

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

5 tab, solder lug and 12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0