# NSN 5930-01-341-9034

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-341-9034

# **Body Style:**

Panel mounted

## Hazardous Locations/environmental Protection:

Dustproof and shock resistant and vibration resistant

### **Overall Length:**

3.120 inches

#### **Overall Height:**

1.000 inches

#### **Overall Width:**

1.000 inches

- **Body Length:**
- 2.850 inches

Body Width:

#### 0.920 inches

**Body Height:** 

# 0.920 inches

Case Material:

Metal

Actuator Length:

0.640 inches

#### **Actuator Style:**

Rectangular

#### Actuator Height:

0.270 inches

#### Actuator Width:

0.640 inches

#### Actuator Color:

Black single actuator

#### Illuminated Actuator Color:

Black single actuator

#### **Actuator Inscription:**

Lamp test (green) single actuator

# Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

## **Features Provided:**

Actuator seal and full display lens

# Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# NSN 5930-01-341-9034

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

## **Special Features:**

Inscription appears green when illuminated

# Precious Material And Location:

Contacts silver

# Terminal Type And Quantity:

5 tab, solder lug and 6 turret

## Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A053a0