

View Online at <https://aerobasegroup.com/nsn/5930-01-341-9551>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

Between 0.342 inches and 0.362 inches

Body Length:

0.652 inches

Body Width:

0.500 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.105 inches and 0.125 inches

Actuator Height:

Between 0.400 inches and 0.420 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

An/alm233 se, test consol, el

Mounting Surface To Terminal End Distance:

0.571 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

3 pole, single throw, double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive ac and 6.000 amperes resistive dc

Precious Material And Location:

Contacts and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0