

View Online at <https://aerobasegroup.com/nsn/5930-01-342-0405>

Thread Class:

2a single pressure connection

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Overall Length:

3.000 inches

Outside Diameter:

0.500 inches single connection

Body Diameter:

1.600 inches

Body Length:

2.500 inches

Overall Diameter:

1.900 inches

Pressure Switch Type:

Gage

Mounting Method:

Terminal, wire-lead

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

25.0 milliamperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

0.85 actuation point pounds per square inch gage and 0.25 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Special Features:

Pressure port threaded internal 0.190-32unf-2b

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0