

View Online at <https://aerobasegroup.com/nsn/5930-01-342-2777>

Thread Class:

2a single mounting facility

Thread Length:

0.534 inches single mounting facility

Hazardous Locations/environmental Protection:

Salt spray resistant and shock resistant and vibration resistant and water resistant and fungus resistant

Overall Length:

3.060 inches

First Flat Length:

0.430 inches 2nd actuator

Flat Height:

0.216 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.530 inches 2nd actuator

Overall Diameter:

0.760 inches

Individual Section Quantity:

2

Operating Temperature Range:

-65.0/+125.0 degrees celsius

End Application:

Milstar system

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section front

Throw Quantity:

4 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

7.5 highest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

4 2nd actuator

Shaft Type:

Round, flatted, threaded hole 1st actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees 2nd actuator

Detent Rotational Torque Range:

+0.312/+1.000 inch-ounces single actuator

Contact Load Current Rating:

30.0 milliamperes resistive load highest dc voltage rating at sea level

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0