NSN 5930-01-342-3941

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-342-3941

| Panel mounted |
|---|
| Hazardous Locations/environmental Protection: |
| Dustproof and shock resistant and vibration resistant |
| Overall Length: |
| 3.120 inches |
| Overall Height: |
| 1.000 inches |
| Overall Width: |
| 1.000 inches |
| Body Length: |
| 2.850 inches |
| Body Width: |
| 0.920 inches |
| Body Height: |
| 0.920 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.640 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.270 inches |
| Actuator Width: |
| 0.640 inches |
| Actuator Color: |
| Black single actuator |
| Illuminated Actuator Color: |
| Black single actuator |
| Actuator Inscription: |
| Slow single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Actuator seal and full display lens |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| |

NSN 5930-01-342-3941

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Inscription appears white when illuminated

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0