

View Online at <https://aerobasegroup.com/nsn/5930-01-342-5789>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Shock proof

**Overall Length:**

4.906 inches

**Overall Height:**

2.875 inches

**Overall Width:**

2.500 inches

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

1.062 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.062 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level110.0 lowest ac voltage rating at sea level250.0 highest dc voltage rating at sea level115.0 lowest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes inductive load highest ac voltage rating at sea level4.0 amperes inductive load lowest ac voltage rating at sea level200.0 milliamperes inductive load highest dc voltage rating at sea level1.5 amperes inductive load lowest dc voltage rating at sea level

**Special Features:**

Legend plate reads stow I2 I3 I4

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0