

View Online at <https://aerobasegroup.com/nsn/5930-01-342-5789>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Shock proof

Overall Length:

4.906 inches

Overall Height:

2.875 inches

Overall Width:

2.500 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

1.062 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.062 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level110.0 lowest ac voltage rating at sea level250.0 highest dc voltage rating at sea level115.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes inductive load highest ac voltage rating at sea level4.0 amperes inductive load lowest ac voltage rating at sea level200.0 milliamperes inductive load highest dc voltage rating at sea level1.5 amperes inductive load lowest dc voltage rating at sea level

Special Features:

Legend plate reads stow I2 I3 I4

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0